



Product: Top Beam Clamp  
 Material: Malleable Iron  
 Finish: Hot Dip Galvanized

EVT#	Trade Size	Shelf QTY	Master QTY
BC11	M8	*	100
BC12	M10	*	100
BC13	M12	*	80

Application: Clamps on beam, girder or similar structure to provide amounting base



Product: Super Flexible Conduit  
 Test Report: BS EN 61386-23:2004, IEC 61386-1:2008  
 Certificate: CE  
 Material: Steel  
 Finish: Galvanized

Application: used primarily in dry areas where it would be impractical to install non-flexible conduit

EVT#	Trade Size	Diameter(mm)		Inside Bend Radius(mm)	Operating Temperature Range	IP Rating	Meters / Coil
		Internal	External				
BSGF10	10mm	7.0	9.0	25	-50°C to +300°C	IP40	50
BSGF12	12mm	10.0	13.0	29	-50°C to +300°C	IP40	50
BSGF16	16mm	13.0	16.0	33	-50°C to +300°C	IP40	50
BSGF20	20mm	17.0	20.5	36	-50°C to +300°C	IP40	50
BSGF25	25mm	21.0	25.0	40	-50°C to +300°C	IP40	50
BSGF32	32mm	28.5	32.0	48	-50°C to +300°C	IP40	25
BSGF40	40mm	37.5	41.5	59	-50°C to +300°C	IP40	25
BSGF50	50mm	48.5	53.0	72	-50°C to +300°C	IP40	25
BSGF308	3/8"	9.0	11.5	28	-50°C to +300°C	IP40	50
BSGF102	1/2"	12.5	15.0	32	-50°C to +300°C	IP40	50
BSGF508	5/8"	15.5	18.0	35	-50°C to +300°C	IP40	50
BSGF304	3/4"	19.0	22.0	37	-50°C to +300°C	IP40	50
BSGF100	1"	25.0	28.0	44	-50°C to +300°C	IP40	50
BSGF114	1-1/4"	32.0	34.0	52	-50°C to +300°C	IP40	25
BSGF112	1-1/2"	38.0	40.0	58	-50°C to +300°C	IP40	25
BSGF200	2"	50.0	53.0	73	-50°C to +300°C	IP40	25




Product: Flexible Adaptor  
 Material: Brass  
 Finish: Self Color

EVT#	Trade Size	Shelf QTY	Master QTY
BSFA1	20mm	*	400
BSFA2	25mm	*	300
BSFA3	32mm	*	200

Application: for use to connect flexible conduits to boxes

Note: supplied with retaining screw and lock nut



Product: PVC Coated Flexible Conduit  
 Test Report: BS EN 61386-23:2004, IEC 61386-1:2008  
 Certificate: CE  
 Material: Steel  
 Finish: Galvanized, with PVC Coated

Application: used primarily in wet/hostile areas where it would be impractical to install non-flexible conduit

EVT#	Trade Size	Diameter(mm)		Inside Bend Radius(mm)	Operating Temperature Range	IP Rating	Meters / Coil
		Internal	External				
BSPF10	10mm	7.0	10.0	25	-15°C to +75°C	IP54	50
BSPF12	12mm	10.0	14.0	30	-15°C to +75°C	IP54	50
BSPF16	16mm	13.0	17.0	40	-15°C to +75°C	IP54	50
BSPF20	20mm	17.0	21.5	45	-15°C to +75°C	IP54	50
BSPF25	25mm	21.0	26.0	55	-15°C to +75°C	IP54	50
BSPF32	32mm	28.5	34.0	70	-15°C to +75°C	IP54	25
BSPF40	40mm	37.5	43.5	80	-15°C to +75°C	IP54	25
BSPF50	50mm	48.5	55.0	90	-15°C to +75°C	IP54	25
BSPF308	3/8"	9.0	12.0	28	-15°C to +75°C	IP54	50
BSPF102	1/2"	12.5	16.0	33	-15°C to +75°C	IP54	50
BSPF508	5/8"	15.5	19.0	41	-15°C to +75°C	IP54	50
BSPF304	3/4"	19.0	23.0	45	-15°C to +75°C	IP54	50
BSPF100	1"	25.0	29.0	60	-15°C to +75°C	IP54	50
BSPF114	1-1/4"	32.0	36.0	75	-15°C to +75°C	IP54	25
BSPF112	1-1/2"	38.0	42.0	80	-15°C to +75°C	IP54	25
BSPF200	2"	50.0	55.0	125	-15°C to +75°C	IP54	25